




Build  
Your  
Dreams  
NEW  
ENERGY



**BYD COMPANY LIMITED**

Address: No.3009, BYD Road, Pingshan, Shenzhen, 518118, P.R.China

**Global Contact**

Email: [eubattery@byd.com](mailto:eubattery@byd.com)

Web: [www.byd.com/energy](http://www.byd.com/energy)

Tel: +86-89888888-61801/61579 /61581

 [Facebook.com/bydcompany](https://www.facebook.com/bydcompany)

 [Twitter.com/bydcompany](https://twitter.com/bydcompany)

 [Youtube.com/bydcompany](https://www.youtube.com/bydcompany)

BYD reserves the right to modify the parameters without prior notice



## Safe Battery Chemistry

---

B-Box is designed with  $\text{LiFePO}_4$  chemistry battery which has been widely recognized as one of the safest battery technologies.  $\text{LiFePO}_4$  chemistry features stable structures and its thermal runaway temperature is over  $480^\circ\text{C}$ . That's 100% higher than NCM and NCA chemistry. It is designed for residential and commercial applications with absolute safety.

## Railway and Automotive Standard Battery

---

As the world's largest Electric Vehicle manufacturer, BYD brings railway and automotive battery standards to residential and commercial solutions: B-Box. 6+ years' track records of large scale applications in Electric Vehicles ensure its safety and reliability. All products have been certified according to international standards including TUV, UL and CE.

## High Power Output

---

B-Box has the highest output power in industry, which brings the highest performance to customers. The system is able to reach C rate at max 1C and 2C at peak to support critical loads such as A/C and pumps, etc.

## Easy Installation and Uninterruptible Maintenance

---

All B-Box systems have modular design featuring uninterruptible maintenance, and easy installation.

## Flexible Extension Life Time

---

B-Box is equipped with modular design and smart BMS (Battery Management System), allowing extension throughout its lifetime.

## Natural Cooling

---

B-Box is designed with natural cooling providing optimum efficiency.

## 10 Years Warranty

---

10 Years Warranty provides the best guarantee of operation.

# BYD B-Box BATTERY STORAGE

B-Box HV



Model	B-Box H 6.4	B-Box H 7.7	B-Box H 9.0	B-Box H 10.2	B-Box H 11.5
Battery Type	LiFePO <sub>4</sub>				
Battery Module	B-Plus-H (1.28 kWh)				
	5 modules	6 modules	7 modules	8 modules	9 modules
Usable Energy <sup>[1]</sup> [kWh]	6.40	7.68	8.96	10.24	11.52
Max Output Power [kW]	6.40	7.68	8.96	10.24	11.52
Peak Output Power [kW]	12.8, 5mins	15.36, 5mins	17.92, 5mins	20.48, 5mins	23.04, 5mins
Round-Trip Efficiency	≥ 95.3% (Under test condition [1] )				
Nominal Voltage [V]	256	307	358	409	460
Operating Voltage Range [V]	200~282	240~338	280~395	320~451	360~500
Communication	CAN / RS485				
Dimension [W × H × D, mm]	580 × 894 × 380	580 × 1014 × 380	580 × 1134 × 380	580 × 1254 × 380	580 × 1374 × 380
Net Weight [kg]	148	174	200	226	252
Enclosure Protection Rating	IP55				
Warranty	10 years				
Ambient Temperature Range <sup>[2]</sup> [°C]	-10 ~ +50				
Certification & Safety Standard	CE / UL1642 / RCM / Sicherheitsleitfaden Li-Ionen-Hausspeicher				
Scalability	Max. 5 systems in parallel (Available for Q1, 2018)				
Compatible Inverters	SMA / KOSTAL, more brands to be announced				

[1] Test conditions: 100% DOD, 0.5C charge & discharge @+25 °C

[2] -10 °C ~ -10 °C will be derating

\*System Usable Energy may be variant with different inverter brands

*Build Your Dreams*

# BYD B-Box BATTERY STORAGE

## B-Box LV Professional



B-Box Pro 2.5~10.0



B-Box Pro 13.8

Model	B-Box Pro 2.5	B-Box Pro 5.0	B-Box Pro 7.5	B-Box Pro 10.0	B-Box Pro 13.8
Battery Type	LiFePO <sub>4</sub>				
Battery Module	1 module	B-Plus 2.5 (2.56 kWh) 2 modules    3 modules		4 modules	B-Plus 13.8 (13.8 kWh)
Usable Energy <sup>[1]</sup> [kWh]	2.56	5.12	7.68	10.24	13.8
Max Output Power [kW]	2.56	5.12	7.68	10.24	12.8
Peak Output Power [kW]	5.12, 30s	10.24, 30s	15.36, 30s	20.48, 30s	13.3, 60s
Round-Trip Efficiency	≥95.3% (Under test condition [1] )				
Nominal Voltage [V]	51.2				
Operating Voltage Range [V]	43.2~56.4				
Communication	CAN / RS485				
Dimension [W × H × D, mm]	600×883×510				650×800×550
Net Weight [kg]	79	113	147	181	175
Enclosure Protection Rating	IP20				
Warranty	10 years				
Ambient Temperature Range <sup>[2]</sup> [°C]	-10 ~ +50				
Certification & Safety Standard	TUV / CE / UN38.3 Sicherheitsleitfaden Li-Ionen-Hausspeicher				CE / RCM / UN38.3
Scalability	Max. 8 B-Box Pro 10.0 systems in parallel				Max. 32 systems in parallel
Compatible Inverters	SMA / GOODWE / SOLAX / Victron, more brands to be announced				

[1] Test conditions: 100% DOD, 0.5C charge & discharge @+25°C

[2] -10°C ~ -10°C will be derating

\*System Usable Energy may be variant with different inverter brands

*Build Your Dreams*

# BYD B-Box BATTERY STORAGE

## B-Box Compact



Model	B-Box Compact 2.5
Battery type	LiFePO <sub>4</sub>
Battery module	B-Plus 2.5 (2.56 kWh) 1 module
Usable Energy <sup>[1]</sup> [kWh]	2.56
Max Output Power [kW]	2.56
Peak Output Power [kW]	5.12, 30s
Round-Trip Efficiency	≥ 95.3% (Under test condition [1])
Nominal Voltage [V]	51.2
Operating Voltage Range [V]	43.2~56.4
Communication	CAN / RS485
Dimension [W×H×D,mm]	483×130×478
Net Weight of B-Plus [kg]	34
Net Weight [kg]	38
Enclosure Protection Rating	IP20
Warranty	10 years
Ambient Temperature Range <sup>[2]</sup> [°C]	-10 ~ +50
Certification & Safety Standard	TUV / CE / RCM / UN38.3
Scalability	Max. 2 B-Plus 2.5 in parallel
Compatible Inverters	SMA / GOODWE / SOLAX / Victron, more brands to be announced

[1] Test conditions: 100% DOD, 0.5C charge & discharge @+25 °C

[2] -10 °C ~ 10 °C will be derating

[3] Max. 32 B-Plus 2.5 in parallel with cabinet design

\*System Usable Energy may be variant with different inverter brands